

# SERIE / SERIES AM 04 - AM 26



**AM 04**



**AM 26**



*Supporto da banco rotante  
Rotating table stand*



*Predisposizione per  
applicazione a parete  
Predisposition for  
wall application*



*Plancia per fissaggio a parete  
Plank for wall mounting*



*Cilindrico, carico dall'alto, corpo e coperchio in acciaio, cilindro interno in acrilico.*

*Predisposto per utilizzo a parete con supporto da parete in dotazione.*

*Per AM 04 è previsto l'utilizzo del solo scarico CR 12.2 nelle varie finiture, mentre per AM 26 è possibile  
Versione standard con bocchetta scarico modello CR 11.1 monoblocco con palottino correzione peso incorporato.  
Versione BS con bocchetta scarico modello CR 12.1 in due componenti con palottino correzione peso separato.*

*A richiesta (mantenendo i diametri indicati) può essere prodotto con dimensioni e capacità specifiche.*

## **OPZIONI A RICHIESTA**

*Finitura cromata, dorata o verniciata con colore specifico*

*Utilizzo in appoggio con supporti fissi o girevoli da 1 a 4 posti*

## **Dimensione e Capacità standard / Standard Size and Capacity**

**AM 04**

Modello	Diametro	Altezza totale	Capacità lt.
Model	Diameter	Total height	Capacity lt.
AM 04.1	140	440	1,5
AM 04.2	160	560	3
AM 04.3	200	700	5

**AM 26**

Modello	Diametro	Altezza totale	Capacità lt.
Model	Diameter	Total height	Capacity lt.
AM 26.1	140	680	3
AM 26.2	160	680	4
AM 26.3	200	680	6



*Cylindrical, top loading, body and lid in steel, internal cylinder in acrylic.*

*Prepared for use on the wall with the supplied wall bracket.*

*For AM 04 it is foreseen the use of only the CR 12.2 unloading in the various finishes, for AM 26 it is possible  
Standard version with monobloc model CR 11.1 unloading system with built-in weight correction device.  
BS version with two-piece CR 12.1 unloading system with separate weight correction system.*

*This dispenser (keeping the indicated diameters), on demand can be customized according to customers' requirements.*

## **OPTIONS ON DEMAND**

*Chrome, gold or painted finish with specific colour*

*Use in support with fixed or revolving supports from 1 to 4 places*