

SERIE / SERIES AM 170



STANDARD




BS version



Predisposizione per applicazione a parete
Predisposition for wall application



Supporto da parete
Wall support



Convogliatore caffè mobile
Mobile coffee conveyor



Corpo in acciaio lucido, carico dall'alto con coperchio appoggiato, vetro frontale piano camera di esposizione e scivolo convogliatore interno rimovibili.

Predisposto per utilizzo a parete con supporto da parete in dotazione.

Versione standard con bocchetta scarico modello CR 11.1 monoblocco con palottino correzione peso incorporato.

Versione BS con bocchetta scarico modello CR 12.1 in due componenti con palottino correzione peso separato.

A richiesta, dove possibile, può essere prodotto con dimensioni e capacità specifiche.

OPZIONI A RICHIESTA

Fronte rivestito in ottone (solo per versione BS)

Fronte con doratura galvanica

Fronte verniciato con colore specifico

Può essere prodotto, a richiesta, con capacità di kg. 12 e maggiori e, sempre a richiesta, può essere prodotto con dimensioni e capacità specifiche.

Dimensione e Capacità standard / Standard Size and Capacity

Modello base	Dimensione mm / Size mm			Capacità kg
Modello	Fronte / Front	Prof. / Depth	Alt. / Height	Capacity kgs
AM 170.1	180	160	500	3,5
AM 170.2	180	200	500	4,5
AM 170.3	180	160	700	5,5
AM 170.6	180	250	700	8,5



Polished steel body, top loading with on top lid, removable flat front glass, display chamber and coffee conveyor chute.

Prepared for wall use with wall bracket supplied.

Standard version with monobloc model CR 11.1 unloading system with built-in weight correction device.

BS version with two-piece CR 12.1 unloading system with separate weight correction system.

On demand, where possible, it can be manufactured with specific dimensions and capacities.

OPTIONS ON DEMAND

Brass covered front (only for BS version)

Front with galvanic gilding

Painted front with specific color

It can be produced, on request, with capacity of kg. 12 and more and moreover this dispenser can be customized according to customers' requirements.

